



Wooden Spiral Staircase Type "Capri Plus"

(with extra treads)

 **1001 Stairs**

www.1001stairs.com

Wooden Spiral Staircase Type “Capri Plus”

- The Capri Plus staircase has a top specification and an excellent build quality and it costs a lot less than other models with a similar specification.
- Includes luxury wooden handrail that co-ordinates with wooden treads.
- Standard staircase is suitable for floor to floor heights from 2320mm to 2760mm.
- Additional treads are available to increase total floor to floor height to a maximum 3680mm.
- Diameters : 1200, 1400 or 1600mm.
- The treads and landing platform are made from a type of hardwood called beech – just like most other kit stairs. However, the Capri Plus uses a grade of wood known as “1st choice”.
- This means that only the best pieces of wood are used to so that there are very few knots or imperfections in them.
- The 40mm treads and landing platform are protected with at least two coats of a tough polyurethane varnish for a great looking finish that will last a long time.
- Wood finish : natural beech or walnut
- Another example of the superior build quality is that the small connectors that join the balusters to the handrail are stainless steel rather than cheap plastic.
- It is lots of small touches like these which really set the Capri Plus spiral staircase kit apart from most other kit spiral stairs.
- Metal finish : white, grey or black.
- A complete easy to follow installation guide is provided.
- Please call or email for design and/or configuration assistance.



- Stairwell opening needs to be at least 50mm larger than the diameter of the staircase.
- Can be installed clockwise or anticlockwise.
- We recommend customers consult their building control office prior to installing any staircase to check that it fully meets their requirements.

Rises and Treads

- The standard staircase fits a floor-to-floor total height of 2320-2760mm with 12 rises and 11 treads.
- The rise can be adjusted between 210-230mm.



Email : info@1001stairs.com

Total Height	No. of Rises	No. of Treads	
2320-2760mm	12	11	Standard
2730-2990mm	13	12	+1 tread
2940-3220mm	14	13	+2 treads
3150-3450mm	15	14	+3 treads
3360-3680mm	16	15	+4 treads