

Spiral Staircase Type "Trio"



www.1001stairs.com

Spiral Staircase Type "Trio"

- This beautiful custom made staircase combines top quality engineering and Italian design.
- The Trio spiral staircase features a variety of chrome and stainless steel balustrade systems with varnished beech handrails, beech treads and either powder coated steel or beech centre column.
- The standard staircase is suitable for floor to floor heights from 2520mm to 2760mm.
- Additional treads are available to increase total floor to floor height to a maximum 3680mm.
- Available diameters : 1200, 1300, 1400, 1500, 1600 or 1800mm.
- The choice of high quality stainless steel balustrade systems make the Trio spiral staircase a sophisticated and stylish solution for any home or commercial interior.
- The Trio has beech hardwood treads and matching beech handrail.
- Treads are manufactured from solid beech with a choice of finishes - natural beech, walnut, mahogany and wengé.
- The handrail is solid beech stained to match the treads.
- Matching balustrades are available for staircase openings, landings and galleries.
- The Trio Spiral Staircase features balustrade infill made from 10mm diameter stainless steel rods (not the flimsy cable found on inferior kits) which follow the outer curve of the staircase adding to the luxurious effect.
- Choice of metal finishes : white, grey or black.
- Stairwell opening needs to be at least 50mm larger than the diameter of the staircase.
- Can be installed clockwise or anticlockwise.
- We recommend customers consult their building control office prior to installing any staircase to check that it fully meets their requirements.
- A complete easy to follow installation guide is provided.
- Please call or email for design and/or configuration assistance.



Email : info@1001stairs.com



Rises and Treads

- The standard staircase fits a floor-to-floor total height of 2520-2760mm with 12 rises (11 treads + landing platform).
- The rise can be adjusted between 210-230mm.

Total Height	No. of Rises	No. of Treads	
2520-2760mm	12	11	Standard
2730-2990mm	13	12	+1 tread
2940-3220mm	14	13	+2 treads
3150-3450mm	15	14	+3 treads
3360-3680mm	16	15	+4 treads