

Bespoke Spiral Staircase Type "Como"



www.1001stairs.com

Bespoke Spiral Staircase Type "Como"

- The Como spiral staircase range combines classic contemporary design with solid construction.
- The standard staircase fits a floor-to-floor total height of 2520-2760mm with 11 treads + landing platform.
- Extra treads are available to increase floor-tofloor height to a maximum of 3680mm.
- Designed for heavy duty use, the Como spiral staircase is straightforward to assemble and is constructed from high quality materials throughout.
- The balusters and steel centre column risers are finished in a high quality powder coating, which is durable and maintenance free.
- Real wood handrail is standard on the Como range
- The 40mm thick treads are manufactured from solid beech with a choice of 10 standard finishes
 natural beech, light walnut, dark walnut, mahogany, cherry, wengé, bleached white, smokey grey, dove <u>or</u> oak.
- Available with white, grey, dove or black standard metalwork finishes.
- The triangular landing platform is included.
- This beautiful staircase and its accessories are manufactured to order.
- Available in diameters: 1100, 1200, 1300, 1400, 1500, 1600, 1700, 1800, 1900, 2000, 2100 <u>and</u> 2200mm.
- Matching balustrades are available for staircase openings, landings and galleries.
- The stairwell opening needs to be at least 50mm larger than the diameter of the staircase.
- Can be installed clockwise or anticlockwise.
- We recommend customers consult their building control office prior to installing any staircase to check that it fully meets their requirements.
- A complete easy to follow installation guide is provided.
- Please call or email for design and/or configuration assistance.



Email : info@1001stairs.com



Rises and Treads

- The standard staircase fits a floor-to-floor total height of 2520-2760mm with 11 treads + landing platform.
- The rise can be adjusted between 210-230mm.

Total Height	No. of Rises	No. of Treads	
2520-2760mm	12	12	Standard
2730-2990mm	13	13	+1 tread
2940-3220mm	14	14	+2 treads
3150-3450mm	15	15	+3 treads
3360-3680mm	16	16	+4 treads