

Wooden Spiral Staircase Type "Capri Plus"

(with extra treads)



www.1001spiralstairs.com

Wooden Spiral Staircase Type "Capri Plus"

- The Capri Plus staircase has a top specification and an excellent build quality and it costs a lot less than other models with a similar specification.
- Includes luxury wooden handrail that coordinates with wooden treads.
- Standard staircase is suitable for floor to floor heights from 2520mm to 2720mm.
- Additional treads are available to increase total floor to floor height to a maximum 5000mm.
- Diameters : 1100, 1200, 1300, 1400, 1500 or 1600mm.
- Larger diameters up to 2000mm can be made to order.
- The treads and landing platform are made from a type of hardwood called beech – just like most other kit stairs. However, the Capri Plus uses a grade of wood known as "1st choice".
- This means that only the best pieces of wood are used to so that there are very few knots or imperfections in them.
- The 40mm treads and landing platform are protected with at least two coats of a tough polyurethane varnish for a great looking finish that will last a long time.
- Wood finish : a choice from 5 standard finishes white bleached, natural beech, stone, walnut, and wengé.
- It is lots of small touches which really set the Capri Plus spiral staircase kit apart from most other kit spiral stairs.
- Metal finish : parchment white, aluminium grey, taupe or mat black.
- A complete easy to follow installation guide is provided.
- Please call or email for design and/or configuration assistance.

Email : info@1001stairs.com



- Stairwell opening needs to be at least 50mm larger than the diameter of the staircase.
- Can be installed clockwise or anticlockwise.
- We recommend customers consult their building control office prior to installing any staircase to check that it fully meets their requirements.

Rises and Treads

- The standard staircase fits a floor-to-floor total height of 2520-2720mm with 12 rises and 11 treads + the platform.
- The rise can be adjusted between 210-230mm.

Total Height	No. of Rises	No. of Treads	
2100-2300mm	10	9	
2310-2510mm	11	10	
2520-2720mm	12	11	Standard
2730-2930mm	13	12	+1 tread
2940-3140mm	14	13	+2 treads
3150-3350mm	15	14	+3 treads
3360-3560mm	16	15	+4 treads