



Metal Spiral Staircase Type "Firenze"

 **1001 Stairs**

www.1001stairs.com

Metal Spiral Staircase Type “Firenze”

- A strong robust design characterises this spiral staircase.
- The standard kit is suitable for floor-to-floor heights from 2520 to 2720mm.
- Additional treads can be ordered to increase the total floor-to-floor height.
- Available in six widths: 1100, 1200, 1300, 1400, 1500 and 1600mm.
- Larger diameters can be made to order.
- The stairwell opening / available floor space must be at least 50mm larger than the diameter of the staircase ie. 1150, 1250, 1350, 1450, 1550 or 1650mm.
- Can be installed either clockwise or anti-clockwise.
- The standard kit includes 11 treads + platform and stair railing with handrail.
- The landing platform and treads are made from pressed steel. They are powder coated and coloured either parchment white, aluminium grey or mat black.
- The balusters and tread spacers are made from steel tube. They are powder coated and also coloured either parchment white, aluminium grey or mat black.
- The handrail is made from plastic and has a special finish that complements the finish of the metal parts.
- The Firenze is particularly easy to assemble in comparison to other spiral staircase kits because a lot of the small components are already assembled in the factory to save you time on site.
- A wide range of accessories allow you to customise the staircase to your own design.
- We recommend customers consult their building control office prior to installing any staircase to check that it fully meets their requirements.
- A complete easy to follow installation guide is provided.
- Please call or email for design and/or configuration assistance.

Email : info@1001stairs.com



Rises and Treads

- The standard staircase fits a floor-to-floor total height of 2520-2720mm with 12 rises (11 treads + landing platform).
- The rise can be adjusted between 210-230mm.

Total Height	No. of Rises	No. of Treads	
2100-2300mm	10	9	
2310-2510mm	11	10	
2520-2720mm	12	11	Standard
2730-2930mm	13	12	+1 tread
2940-3140mm	14	13	+2 treads
3150-3350mm	15	14	+3 treads
3360-3260mm	16	15	+4 treads