

Luxury Open Staircase Type "Karini"



www.1001spiralstairs.com

Luxury Open Staircase Type "Karini"

- This premium quality contemporary styled modular staircase can be built in straight, L-shaped or U-shaped layouts.
- The Karini staircase is easy to configure and its flexible design suits most space requirements.
- The 8mm Z shaped steel structure on both sides of the staircase creates a solid base for the 40mm beech wood treads.
- The staircase can be configured with 3, 2 or 1 tread(s) winder (corner treads).
- The steel structure is powder coated in 4 standard colours: parchment white, aluminium grey, bronze and black.
- The brushed oiled beech wood treads are available in 5 finishes: untreated, oak, walnut, stone and wengé.
- Additional treads can be ordered incl. fittings to increase the total staircase height (the maximum staircase height is 3740mm).
- Staircase width: 700 mm, 800 mm or 900 mm
- Custom made versions up to 1000 mm wide are also possible.
- The standard staircase configuration is supplied with railing for one side of the staircase (see our accessories for extra railing and balustrade options).
- The standard railing is made from Ø 20 mm vertical steel balusters (powder coated) and a Ø 42 mm synthetic handrail.
- A Ø 50 mm solid wood handrail can also be ordered.
- The metal finish is available in parchment white, aluminium grey, bronze or black.
- Riser bars are recommended when young children may be using the staircase.
- The stairwell must be at least 50 mm larger than the width of the staircase.
- A complete easy to follow installation guidelines are provided.
- We recommend customers consult their local building control office prior to installing any staircase to check that it fully meets their requirements.
- Call or email us for support designing your new staircase

Email : info@1001stairs.com



Rises and Treads

- The standard staircase is suitable for floor-to-floor heights of 2340-2860mm with 12 treads (and 13 rises)
- The rise (distance between two treads) is from 180-220mm.
- The going is from 220-280mm.

| Total Height | No. of Rises | No. of Treads | |
|--------------|-----------------|------------------|-----------|
| 2340-2860mm | 13 | 12 | Standard |
| 2520-3080mm | 14 | 13 | +1 tread |
| 2700-3300mm | 15 | 14 | +2 treads |
| 2880-3520mm | 16 | 15 | +3 treads |
| 3060-3740mm | 17 | 16 | +4 treads |